## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources							
Supplier's name or trade mark: Hera GmbH & Co KG							
Supplier's address: FE, Dieselstraße 9, 32130 Enger Herford, DE							
Model identifier: AR 45-LED							
Type of light source:							
Lighting technology used:		LED	Non-directional or directional:	DLS			
Light source cap-type		nein					
(or other electric	interface)						
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:		Nein	Envelope:	-			
High luminance light source:		Nein					
Anti-glare shield:		Nein	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	G			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		222 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000			
On-mode power (P <sub>on</sub> ), expressed in W		3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90			
	Height Width	50 50	Spectral power distribution in the	See image in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	13	range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	0,421 0,392			
Parameters for directional light sources:							
Peak luminous intensity (cd)		1	Beam angle in degrees, or the range of beam angles that can be set	110			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		0	Survival factor	0,00			
the lumen maintenance factor		0,00					

(a)'-': not applicable; (b)'-': not applicable;

